

PHOENIX

PHPA-2200 & PLPA-2150 AUTOMATIC TURNTABLE STRETCH WRAPPING MACHINES



PHOENIX
LOW PROFILE
PLPA-2150



PHOENIX
HIGH PROFILE
PHPA-2200

www.phoenixwrappers.com



SEMI-AUTO TURNTABLE
STRETCH WRAPPERS



ROTARY ARM STRETCH
WRAPPERS



CUSTOM
AUTOMATED SYSTEMS



HIGH SPEED AUTOMATED
STRETCH WRAPPERS



FULLY INTEGRATED
PACKAGING LINES

PHPA-2200 & PLPA-2150

AUTOMATIC TURNTABLE STRETCH WRAPPING MACHINES



FILM COST SAVINGS

Multiple wrap cycles apply film only where required.

Separate up/down speeds save time & up to 10% reduction of stretch film costs.

Separate top/bottom wrap selections eliminate wasted revolutions of film.

Film saving logic eliminates film waste.



SAFETY MEASURES

Timed, impulse cut wire is only ON when cutting and cold to the touch in seconds.

Not hazardous to operator.

No permanent, constant heat source.

Pneumatic cut & wipe system with no mechanical drive thus, nothing gets caught in mechanical system.



MAINTENANCE WISE

More table support casters than any in its class.

Maintenance-free polymer support bearings for quiet, efficient operation.

Structural angle guard is welded to turntable to protect film clamp when un/loading.

Lifetime Warranty on Pre-stretch Rollers.



DURABLE DESIGN

Dual #50 chain carriage lifting system for unprecedented safety.

HSS formed steel tower to protect lifting & rotation motors.

Solid "cold rolled" steel carriage guide bars welded in the tower.

Top quality commercially available components.

Meets all Cdn & US standards with cUL Approval.

NOTHING BEATS THE BEST IN CLASS!

Auto Cut, Wipe & Film Tail Treatment:

Pneumatic system cuts (not tears), wipes, and brushes film to load...no film tail!

Heavier:

Built to last...the 5000 lbs. std. weight capacity is the heaviest in its class.

Faster:

At 15RPM, it's the fastest wrapping speed in its class. Wrap more loads...faster.

Ultimate Control:

Best in Class controls. Simple yet powerful controls offer wrap flexibility and film savings.



AUTO CUT & WIPE, HEAVIER & FASTER...BEST IN CLASS!

GENERAL SPECIFICATIONS

Wrapping Speed Variable up to 15RPM

Load Diagonal Max. 80"

Load Weight Max. 5000 lbs.

Load Height Up to 80"

Wrap Tension Variable

Power Requirement 120 Vac. 15 Amp

Controls

3 Wrap Programs

Wrap up & Wrap up/ Down

Top Cover Pause

Up/Down Speeds carriage Separate

Top & Bottom Wrap Counters Separate 1-9 count

Control Settings Password Protected

Warranty

3 years-All Parts / 10 years-Frame

Lifetime warranty on Pre-stretch Rollers

Turntable

	PHPA-2200	PLPA-2150
Support Casters	9 H.D.	28 H.D.
Height	8" 3/4	2" 7/8
Size	48"x48" (octagon)	67" diameter
Forklift Portable	Front & Back	Front

*Specifications subject to change without notice

Phoenix...**Best in Class** performance
at a **Best in Class** price!

www.phoenixwrappers.com

Get the Facts and Compare!
(514) 956-1525

